

# Material Safety Data Sheet

Date last revised April, 2001

<b>I. GENERAL INFORMATION</b>		
Chemical Name & Synonyms SILICONE SEALANT	Trade Name & Synonyms PECORA 896	
Chemical Family POLYDIMETHYLSILOXANE MIXTURE	Formula MIXTURE	
Proper DOT Shipping CALKING COMPOUND	DOT Hazard Classification NONE	
Manufacturer PECORA CORPORATION	Manufacturer's Phone Number 215-723-6051	
Manufacturer's Address 165 Wambold Road, Harleysville, PA 19438	Chemtrec Phone Number 800-424-9300	
<b>II. INGREDIENTS</b>		
Principal Hazardous Components SILICONE DIOXIDE (CAS # 7631-86-9)	Percent 4%	Threshold Limit Value (Units) 10 Mg/M <sup>3</sup> DUST
METHYL OXIMINO SILANE (CAS # 22984-54-9)	4 %	NONE ESTABLISHED
THIS PRODUCT DOES NOT CONTAIN ANY TOXIC CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF SARA AND 40 CFR, PART 372.		
HEALTH 1	FLAMMABILITY 0	REACTIVITY 0
<b>III. PHYSICAL DATA</b>		
Boiling Point (°F) N/A	Specific Gravity (H <sub>2</sub> O = 1) 1.22	
Vapor Pressure (mm Hg.) UNKNOWN	Percent Volatile by Volume (%) < 3%	
Vapor Density (Air = 1) HEAVIER	Evaporation Rate (ETHER = 1) SLOWER	
Solubility in Water INSOLUBLE	pH N/A	
Appearance & Odor SMOOTH PASTE – MILD, SLIGHTLY SOLVENT - LIKE ODOR		
<b>IV. FIRE &amp; EXPLOSION HAZARD DATA</b>		
Flash Point (Test Method) > 220° F.	Auto Ignition Temperature UNKNOWN	
Flammable Limits UNKNOWN	LEL NOT DETERMINED	UEL NOT DETERMINED
Extinguishing Media: DRY CHEMICAL, WATER SPRAY, FOAM, CARBON DIOXIDE		
Special Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS WHEN FIGHTING FIRES THAT CONTAIN CHEMICALS.		
Unusual Fire & Explosion Hazards: UNDER FIRE CONDITIONS, IRRITATING OR TOXIC VAPORS MAY BE PRESENT		

**V. Health Hazard Data**

OSHA Permissible Exposure Limit SEE SECTION II	ACGIH Threshold Limit Value SEE SECTION II
Carcinogen – NTP Program NO	Carcinogen – IARC Program NO
Symptoms of Exposure: VAPORS EMITTED AS THE SEALANT CURES MAY IRRITATE THE EYES, NOSE AND THROAT PARTICULARLY IN AN ENCLOSED OR POORLY VENTILATED AREA. DIRECT CONTACT WITH THE UNCURED PRODUCT MAY IRRITATE THE EYES AND MOUTH.	
Medical Conditions Aggravated By Exposure: PRECLUDE FROM EXPOSURE THOSE INDIVIDUALS HAVING A HISTORY OF RESPIRATORY ILLNESS OR PRE-EXISTING EYE OR SKIN CONDITIONS.	
Primary Route (s) of Entry: INHALATION AND SKIN OR EYE CONTACT	
Emergency First Aid: INHALATION: MOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, GIVE OXYGEN. CALL A PHYSICIAN. SKIN: REMOVE UNCURED MATERIAL AND WASH WITH SOAP AND WATER. EYES: FLUSH WITH RUNNING WATER FOR 15 MINUTES. CONSULT A PHYSICIAN. INGESTION: CONSULT A PHYSICIAN IMMEDIATELY.	

**VI. REACTIVITY DATA**

Stability		Unstable	Conditions to Avoid
	X	Stable	WATER AND HIGH TEMPERATURES
Incompatibility			Materials to Avoid WATER AND STRONG ACID
Hazardous		May Occur	Conditions to Avoid
	X	Will Not Occur	HIGH HUMIDITY AND HIGH TEMPERATURES
Polymerization			
Hazardous Decomposition Products: OXIDES OF CARBON, SILOXANE AND POSSIBLY OTHER FUMES WHICH MAY BE TOXIC.			

**VII. ENVIRONMENTAL PROTECTION PROCEDURES**

Spill Response: COVER WITH DRY ABSORBENT MATERIAL SUCH AS SAND OR DIRT. PICK UP AND PLACE IN A CONTAINER FOR DISPOSAL.
Waste Disposal Method: LAND FILL OR INCINERATE IN ACCORDANCE WITH FEDERAL, STATE OR LOCAL ENVIRONMENTAL CONTROL REGULATIONS.

**VIII. SPECIAL PROTECTION INFORMATION**

Eye Protection NONE NORMALLY REQUIRED	Skin Protection NONE NORMALLY REQUIRED
Respiratory Protection (Specific Type) ORGANIC VAPOR RESPIRATOR IN CONFINED AREAS	Ventilation Recommended LOCAL VENTILATION
Other Protection: SAFETY GLASSES FOR OVERHEAD APPLICATIONS.	

**IX. SPECIAL PRECAUTIONS**

Hygienic Practices In Handling & Storage: TO PROLONG SHELF LIFE, STORE AT TEMPERATURE BELOW 80° F. WASH HANDS AFTER USE. STORE IN DRY AREA AWAY FROM HEAT.
Precautions For Repair & Maintenance of Contaminated Equipment: SEE SECTION V
Other Precautions:

**KEEP OUT OF REACH OF CHILDREN!!!!**