

# Pecora-Deck™ 850

Accelerator

## Specification Data Sheet



### 1. BASIC USES

Pecora-Deck™ 850 Accelerator will reduce the cure time when the temperature is between 40° and 70°F.

### 2. MANUFACTURER

Pecora Corporation  
165 Wambold Road  
Harleysville, PA 19438  
Phone: 215-723-6051  
800-523-6688  
Fax: 215-721-0286  
Website: [www.pecora.com](http://www.pecora.com)

### 3. PRODUCT DESCRIPTION

Pecora-Deck™ 850 Accelerator is designed to speed the cure of Pecora Deck Coatings. This product is especially useful at temperatures of 40 to 70°F (4 to 21°C), where the cure rate can be sluggish. The cure time of moisture-cured urethanes is highly dependent on temperature and humidity. Below 40°F (4°C), the cure time may be very long, even with the use of Pecora 850 Accelerator. Please be sure that each layer is cured to a firm, rubbery film before proceeding with application of the next coat.

### PACKAGING

- 4 ounce vial

### 4. INSTALLATION

**Usage:** Add one 4 oz. can to a five gallon pail of coating and stir thoroughly. If using one gallon cans, carefully measure 0.8 oz.

per gallon using a clean measuring cup. Mix thoroughly. Avoid drawing air into the coating during stirring.

**Precautions:** Uncured epoxy compounds may produce irritation following frequent and prolonged contact with the skin. Before use, refer to MSDS for important warnings and safety information. Avoid contact with skin, eyes or clothing. The use of gloves, aprons or other protective devices is recommended. In case of skin contact, wash thoroughly with soap and water. If contact with eyes is made, flush thoroughly with clear water and get medical attention.

**Storage Life:** 12 months from date of manufacture when stored at 85°F or below.

**FOR PROFESSIONAL USE ONLY.  
KEEP OUT OF THE REACH  
OF CHILDREN.**

### 5. AVAILABILITY AND COST

Pecora products are available from stocking distributors nationwide. For the name and telephone number of your nearest representative, call the number below or visit our website at [www.pecora.com](http://www.pecora.com).

### 6. WARRANTY

Pecora Corporation warrants its products to be free of defects. Under this warranty, we will provide, at no charge, replacement materials for, or refund the purchase price of, any product proven to be defective when used in strict accordance with our

published recommendations and in applications considered by us as suitable for this product. The determination of eligibility for this warranty, or the choice of remedy available under this warranty, shall be made in our sole discretion and any decisions made by Pecora Corporation shall be final. This warranty is in lieu of any and all other warranties, expressed or implied, including but not limited to a warranty of merchantability or fitness for a particular purpose and in no case will Pecora be liable for damages other than those expressly stated in this warranty, including but not limited to incidental or consequential damages.

### 7. MAINTENANCE

Non-Applicable.

### 8. TECHNICAL SERVICES

Pecora representatives are available to assist you in selecting an appropriate product and to provide on-site application instructions. For further information and assistance, please call our Technical Service Department at 800-523-6688.

### 9. FILING SYSTEMS

- Sweet's Catalog File: [www.sweets.com](http://www.sweets.com)
- General Building
  - 07100 Waterproofing
  - 07920 Sealants
- Civil Engineering
  - 07100 Waterproofing



Since Pecora architectural sealants are applied to varied substrates under diverse environmental conditions and construction situations it is recommended that substrate testing be conducted prior to application.



PEOPLE • PRODUCTS • PERFORMANCE

[www.pecora.com](http://www.pecora.com)

PEC153  
9/07

165 Wambold Road, Harleysville, PA 19438  
Phone: 800-523-6688 • 215-723-6051 • FAX: 215-721-0286