



LEED Certification Data

To Whom It May Concern,

We at Pecora are totally committed to developing customer-valued adhesive, sealant and waterproofing solutions. Our focus is directed toward continuous improvement, superior quality and exceptional service.

Pecora 311 NS Pavement Silicone is manufactured in Harleysville, Pennsylvania. If Harleysville falls within a 500-mile radius of the project site, the product is considered to be a locally produced material and can help contribute to earning Material Credit 5.

The information presented here is the extent of the product information that can be disclosed. The “extraction and/or harvest point” of specific product components is variable.

Pecora 311 NS Pavement Silicone contains <40 g/L volatile organic content (VOC) and therefore satisfies the LEED criteria for Low-Emitting Material Standard Credit 4.

LEED Criteria for VOC content of sealant and adhesive products as defined by:

SCAQMD Rule # 1168 <250 g/L

BAAQMDR Reg. 8 Rule 51 <250 g/L

Should you have any questions or require additional information, please do not hesitate to contact me at 215-799-7520.

Sincerely,

A handwritten signature in black ink, appearing to read 'Roy D. Cannon, Jr.'.

Roy D. Cannon, Jr.
Technical Service Director
Pecora Corporation

'USGBC' and related logo is a trademark owned by the U.S. Green Building Council and is used by permission.