



LEED Certification Data

Ref: AVW-920 High Performance Acrylic Latex – LEED Product Information

To Whom It May Concern:

We at Pecora are totally committed to developing customer-valued adhesive, sealant and waterproofing solutions. Our focus is directed toward continuous improvement, superior quality and exceptional service.

Pecora AVW-920 High Performance Acrylic Latex is manufactured in Harleysville, Pennsylvania. If Harleysville falls within a 500-mile radius of the project site, the product is considered to be a locally produced material and can help contribute to earning Material Credit 5.

The information presented here is the extent of the product information that can be disclosed. The “extraction and/or harvest point” of specific product components is variable.

Pecora AVW-920 High Performance Acrylic Latex contains 15 g/L volatile organic content (VOC) and therefore satisfies the LEED criteria for Low-Emitting Materials Standard Credit 4.

LEED Criteria for VOC content of sealant and adhesive products as defined by:

SCAQMD Rule # 1168 <250 g/L

BAAQMDR Reg. 8 Rule 51 <250 g/L

Should you have any questions or require additional information, please do not hesitate to contact me at 215-799-7520.

Sincerely,

A handwritten signature in black ink, appearing to read 'Roy D. Cannon, Jr.'.

Roy D. Cannon, Jr.
Technical Service Director
Pecora Corporation

'USGBC' and related logo is a trademark owned by the U.S. Green Building Council and is used by permission.