



LEED Certification Data

Product Reference: Pecora 53+ Primer

To Whom it May Concern,

We at Pecora are totally committed to developing customer-valued adhesive, sealant and waterproofing solutions. Our focus is directed toward continuous improvement, superior quality and exceptional service.

Pecora 53+ Primer is manufactured in Harleysville, Pennsylvania. If Harleysville falls within a 500-mile radius of the project site, the product is considered to be a locally produced material and can help contribute to earning Material Credit 5.

The information presented here is the extent of the product information that can be disclosed. The “extraction and/or harvest point” of specific product components is variable.

Pecora 53+ Primer contains 782 g/L volatile organic content (VOC) and therefore does not satisfy the LEED criteria for Low-Emitting Material Standard Credit 4.

LEED Criteria for VOC content of sealant and adhesive products as defined by:

SCAQMD Rule # 1168 : Architectural Primers for Porous Substrates. < 775 g/L.

BAAQMDR Reg. 8 Rule 51: Architectural Primers for Porous Substrates. < 775 g/L.

Should you have any questions or require additional information, please do not hesitate to contact me at 215-799-7520.

Sincerely,

A handwritten signature in black ink, appearing to read 'Roy D. Cannon, Jr.'.

Roy D. Cannon, Jr.
Technical Service Director
Pecora Corporation

'USGBC' and related logo is a trademark owned by the U.S. Green Building Council and is used by permission