



LEED Certification Data

Ref: Synthacalk™ GC-2+ LEED Product Information

To Whom It May Concern:

We at Pecora are totally committed to developing customer-valued adhesive, sealant and waterproofing solutions. Our focus is directed toward continuous improvement, superior quality and exceptional service.

Pecora Synthacalk™ GC-2+ is manufactured in Harleysville, Pennsylvania. If Harleysville falls within a 500-mile radius of the project site, the product is considered to be a locally produced material and can help contribute to earning Material Credit 5.

The information presented here is the extent of the product information that can be disclosed. The “extraction and/or harvest point” of specific product components is variable.

Synthacalk™ GC-2 is a 2 part system. The base contains 20 g/L volatile organic content (VOC) and the activator contains 0 g/L volatile organic content (VOC) therefore satisfies the LEED criteria Low-Emitting Material Standard Credit 4.

LEED Criteria for VOC content of sealant and adhesive products as defined by:

SCAQMD Rule # 1168 <250 g/L

BAAQMDR Reg. 8 Rule 51 <250 g/L

No off gassing occurs with the Synthacalk™ GC-2+after 24 hrs. of cure.

Pecora Synthacalk polysulfide sealant contains 0% recyclable content.

Should you have any questions or require additional information, please do not hesitate to contact me at 215-799-7520.

Sincerely,

A handwritten signature in black ink, appearing to read 'Roy D. Cannon, Jr.'.

Roy D. Cannon, Jr.
Technical Service Director
Pecora Corporation

'USGBC' and related logo is a trademark owned by the U.S. Green Building Council and is used by permission



'USGBC' and related logo is a trademark owned by the U.S. Green Building Council and is used by permission

165 Wambold Road, Harleysville, PA 19438 • 1-800-523-6688 • 215-723-6051 • FAX 215-721-0286