



Green Building Certification Data

RE: Pecora 890FTS and 890FTS-TXTR Field Tintable Non-Staining Silicone Sealant – Smooth and Textured Formulas

March 9, 2016

To Whom It May Concern:

This will certify the following information for Pecora 890FTS and 890FTS-TXTR.

LEED® 2009 and LEED® v4:

MR Credit 4.1 and 4.2, Recycled Content (*BPDO-Sourcing of Raw Materials, Option 2): For the purposes of the LEED Rating System Pecora 890FTS and 890FTS-TXTR each contain 0% recycled content.

MR Credit 5.1 and 5.2, Regional Materials (*BPDO-Sourcing of Raw Materials, Options 1 and 2): Pecora 890FTS and 890FTS-TXTR are manufactured in Harleysville, PA 19438. Due to the complexity of their raw material supply chain, the point source of Pecora 890FTS and 890FTS-TXTR’s material ingredients cannot be determined.

IEQ Credit 4.1, Low-Emitting Materials–Adhesives & Sealants (*Low-Emitting Mat’ls., Option 2): Pecora 890FTS and 890FTS-TXTR each contain 98 g/L volatile organic compound (VOC) content, well below the 250 g/L VOC limit set by South Coast Air Quality Management District (SCAQMD) Rule 1168 (effective 7/1/2005) for architectural sealants.

*LEED v4 credits and options

LEED® for Schools IEQ Credit 4.1, Low-Emitting Materials–Adhesives & Sealants:

Alternative Compliance Path: Conformance with LEED® 2009 for New Construction IEQ Credit 4.1 (above) may be substituted for meeting LEED® for Schools IEQ Credit 4.1 VOC emissions testing requirements; therefore Pecora 890FTS and 890FTS-TXTR will help project teams satisfy this credit.

LEED® v4 for New Construction, Core and Shell, Schools, Retail, Data Centers, Warehouses and Distribution Centers, Hospitality, Healthcare

EQ Credit Low-Emitting Materials, Options 1 and 2: At this time there is no available documentation demonstrating compliance of Pecora 890FTS and 890FTS-TXTR with California Department of Public Health Standard Method v1.1-2010 (CA Specification 01350).

Green Globes for New Construction

Criterion 7.2.1 Volatile Organic Compounds: Pecora 890FTS and 890FTS-TXTR each contain 98 g/L volatile organic compound (VOC), well below the 250 g/L VOC limit set by South Coast Air Quality Management District (SCAQMD) Rule 1168 for architectural sealants.

'USGBC' and related logo is a trademark owned by the U.S. Green Building Council and is used by permission.





Should you require additional information, please contact the Technical Services Dept. at 1-800-355-8817 or techservices@pecora.com.

Sincerely,

A handwritten signature in black ink that reads 'Steven T. Lawrey'.

Steven T. Lawrey AIA, CSI, CCS, CCCA, LEED® AP
Building Science Engineer
Pecora Corporation

'USGBC' and related logo is a trademark owned by the U.S. Green Building Council and is used by permission.

