

PRODUCT DESCRIPTION	PROPERTIES/SPECIFICATIONS			
	Composition	Movement Class	Service Temperature (°F)	Modulus (Tensile At 100% Extension (PSI))
Non-Sag (NS) - Self Leveling (SL) - Pre-Formed (P) - Sprayable (S) Multi-Laminate System (ML) - 1 Part (I) - 2 Part (II)				
Acoustical & Insulation Sealant (NS)(I)	Acrylic	7.5	N/A	20
Flexible Polyurethane Security Sealant (NS)(II)	Urethane	12.5	-20 to 180	180
General Purpose Polyurethane Sealant (NS)(II)	Urethane	50	-20 to 180	28
Non-Sag, Traffic-Grade Polyurethane Sealant (NS)(II)	Urethane	25	-20 to 180	55
Non-Staining Technology™, Architectural Silicone Sealant (NS)(I)	Silicone	50	-60 to 300	38
Self-Leveling Pavement Joint Sealant (SL)(I)	Silicone	100	-60 to 300	9
Non-Sag Pavement Joint Sealant (NS)(I)	Silicone	100	-60 to 300	15
Self-Leveling Parking Deck Sealant (SL)(I)	Silicone	100	-60 to 300	9
Non-Sag Parking Deck Sealant (NS)(I)	Silicone	100	-60 to 300	15
Fast Cure Traffic Silicone (SL)(II)	Silicone	100	-60 to 300	13
Flexible Polyurethane Security Sealant (NS)(II)	Urethane	12.5	-20 to 180	180
Non-Sag, Traffic-Grade Polyurethane Sealant (NS)(II)	Urethane	25	-20 to 180	55
Urethane Pre-Molded Wide Joint Seal (P)	Urethane	25	-20 to 180	45
Self-Leveling Polyurethane Slope Grade (5% & 15%), Traffic-Grade Sealant (SL)(II)	Urethane	25	-20 to 180	45
Self-Leveling, Traffic-Grade Polyurethane Sealant (SL)(II)	Urethane	25	-20 to 180	45
Self-Leveling, Traffic-Grade Hybrid STPU Sealant (SL)(I)	STPU	25	-20 to 180	75
Two-Part Polysulfide Rubber Sealant (NS)(II)	Polysulfide	25	-20 to 180	50
Acoustical & Insulation Latex Sealant (NS/S)(I)	Acrylic	7.5	0 to 180	20
Non-Skinning Butyl Sealant (NS)(I)	Butyl	-	-	N/A
(Fire and Temperature Rated) Acoustical & Insulation Sealant (NS)(I)	Acrylic	7.5	N/A	20
General Purpose Polyurethane Sealant (NS)(II)	Urethane	50	-20 to 180	28
Silane Penetrating Clear Sealer (S)(I)	Silane	N/A	N/A	N/A
Water-Based Penetrating Sealer (S)(II)	Siloxane	N/A	N/A	N/A
Silane Penetrating Sealer (S)(I)	Silane	N/A	N/A	N/A
Elastometric Acrylic Wall Coating (S)(I)	Acrylic	N/A	-15 to 180	N/A
Primerless Silicone Sealant for Air Vapor Barrier Surface Transitions (NS)(I)	Silicone	25	-60 to 300	33
Liquid Applied Flashing and Joint Filler (NS)(I)	STPU	12.5	-20 to 180	120
Fluid Applied, Permeable STPU Air, Vapor & Water Resistive Barrier (S)(I)	STPU	N/A	-20 to 180	30
100% Pre-Formed Silicone Transition Membrane (P)	Silicone	200	-60 to 300	180
Elastometric Deck Coating System (SL)(ML)	Urethane	N/A	-20 to 180	N/A
Low VOC, Fast Cure Elastometric Deck Coating System (SL)(ML)	Urethane	N/A	-20 to 180	N/A



Pecora is a member and supports: SWRI, CSI, AIA, ICRI, ABAA, USGBC, IPI

Pecora is ISO 9001:2008 certified.

The Pecora promise is about more than high quality sealants, air barriers, and traffic coatings. It's a promise to you, to your project, to your reputation. We're hands-on and always here when you need us. Ready to make recommendations, answer questions, work through decisions, and help you find the best solution for your job. It's a promise of partnership.

Since its founding in 1862 as a Philadelphia-based paint and varnish company, Pecora has developed and manufactured trusted solutions to meet every customer's need. Over the years, the company used its innovative technological development capabilities to grow its product line and quickly emerge as a premier manufacturer of architectural weatherproofing products. Pecora is ISO 9001:2008 certified and proudly manufactures all products right here in the USA.

Contact Pecora Technical Services to learn how Pecora products can contribute to LEED, Green Globes, Living Building Challenge, and other green building rating systems.

165 Wambold Road, Harleysville, PA 19438 | 800.523.6688 | pecora.com

SEALANTS

TRAFFIC COATINGS

AIR BARRIERS

PRODUCT NAME	Expansion & Control	Waterproofing	Non-Structural Glazing	Structural Glazing	Shop Glazing	Window Beading	High Impact	Highway	Pedestrian	Vehicular	Airfield	Parking Area	Deck Coatings	Acoustical	Below Grade	Chemical Resistance	Firestopping	Food Processing-USA	Perimeter	Potable Water	Sanitary	Security	Water Immersion	Wall Coatings	APPLICABLE STANDARDS
SEALANTS																									
Pecora 864NST	●		●														●	●	●						ASTM C920, TT-S-001543A, 19-GP9, USDA
Pecora 890NST	●		●															●	●						ASTM C920, TT-S-001543A, 19-GP9, USDA
Pecora 895NST	●		●	●	●	●	●											●	●						ASTM C920, TT-S-001543A, 19-GP9, USDA, ASTM C1184
Pecora 898NST	●		●															●	●		●				ASTM C920, TT-S-001543A, USDA
Pecora 890FTS	●		●															●	●						ASTM C920, TT-S-001543A, 19-GP9, USDA
Pecora 890FTS-TXTR	●		●															●	●						ASTM C920, TT-S-00230C, 19GP-9, USDA
Pecora Contractor Silicone - PCS	●		●		●	●	●											●	●						ASTM C920, TT-S-230C, CGSB-19GP-9, USDA
SilsSpan	●		●															●	●						ASTM C1523, USDA
Dynatrol® I-XL	●		●															●	●						ASTM C920, C1247, NSF61, 00230C, USDA
Dynatrol® I-XL Hybrid	●		●															●	●						ASTM C920, USDA
Dynatrol® II	●								●	●		●		●	●		●	●	●				●		ASTM C920, TT-S-00227E, UL, USDA
Dynaspan	●								●	●		●													ASTM C920, TT-S-00227E
AC-20® + Silicone			●			●												●	●						ASTM C834, USDA
BA-98														●											ASTM C919, ASTM E-90, AAMA 809.2
BC-158	●		●			●								●				●	●						ASTM C1311, TT-S-001657
Synthacalk™ GC2+	●															●		●		●			●		ASTM C920, C1247, NSF61 SECTION 6, USDA
Tilt-Seal™	●	●																●	●						ASTM C920, ASTM C834, USDA
GLAZING																									
AWW920™			●		●	●												●	●						ASTM C920, ASTM C834, USDA
Pecora 860	●		●			●												●	●		●				ASTM C920, TT-S-001543A, FDA, NSF51
Pecora 895NST	●		●	●	●	●	●											●	●						ASTM C920, TT-S-001543A, 19-GP9, USDA, ASTM C1184
Pecora 896	●		●	●	●	●												●	●						ASTM C1184-91, C920, TT-S-001543A, USDA, ASTM C1184
Pecora 896FC		●	●		●	●	●												●						TT-S-001543A, TT-S-002390C, ASTM C920, ASTM C1184
Pecora 896-HIS			●	●	●	●	●															●			AAMA 506.0, TT-S-230C, CLASS A, ASTM C920, ASTM C1184
Pecora 896-SSL		●	●		●																				AAMA 803.3-07 TYPE II
Pecora 896-TBS	●		●	●	●	●												●	●						ASTM C1184-91, C920, T-S-001543A, USDA, ASTM C1184
Pecora 896-TBS-SSL		●	●		●																				AAMA 803.3-07 TYPE II
Pecora 985			●	●	●	●	●											●							ASTM C920, USDA, ASTM C1184
Pecora 1215			●		●																				AAMA 803.3-07 TYPE I & II
SilsSpan	●		●															●	●						ASTM C1523, USDA
XL-Span		●																●	●						ASTM C1523, USDA
SECURITY SEALANTS																									
Pecora 896-HIS			●	●	●	●	●															●			AAMA 506.0, TT-S-230C, CLASS A, ASTM C920, ASTM C1184
Dynaflex	●								●	●							●	●	●			●	●		ASTM C920, TT-S-00227E, UL, ASTM C1247, USDA
Dynaflex SC	●																		●			●			ASTM C920, TT-S-00230C, USDA
Dynapoxy™ EP-1200																		●	●			●			ASTM C881, TYPE I, USDA
Dynatrol® II	●								●	●		●	●	●			●	●	●				●		ASTM C920, TT-S-00227E, UL, USDA

* All sealants used as a component of a UL listed assembly