

PRODUCT DESCRIPTION	PROPERTIES/SPECIFICATIONS			
	Composition	Movement Class	Service Temperature (°F)	Modulus (Tensile At 100% Extension (PSI))
Non-Sag (NS) - Self Leveling (SL) - Pre-Formed (P) - Sprayable (S) Multi-Laminate System (ML) - 1 Part (I) - 2 Part (II)				
Non-Staining Technology™, Architectural Silicone Sealant (NS)(I)	Silicone	50	-60 to 300	38
Non-Staining Technology™, Ultra-Low-Modulus Silicone Sealant (NS)(I)	Silicone	100	-60 to 300	30
Non-Staining Technology™, Silicone Glazing & Weatherproofing Sealant (NS)(I)	Silicone	50	-60 to 300	50
Non-Staining Technology™, Sanitary Mildew Resistant Silicone Sealant (NS)(I)	Silicone	50	-60 to 300	45
Field Tintable Silicone*(NS)(I)	Silicone	100	-60 to 300	30
Field Tintable Textured Silicone* (NS)(I)	Silicone	50	-60 to 300	40
One-Part, Architectural Silicone Sealant (NS)(I)	Silicone	50	-60 to 300	35
Pre-Formed Silicone Profile Seal (P)	Silicone	200	-60 to 300	70
General Purpose Polyurethane Sealant (NS)(I)	Urethane	25	-20 to 180	65
STPU Silicone/Urethane One-Part Hybrid (NS)(I)	STPU	50	-40 to 195	35
General Purpose Polyurethane Sealant (NS)(II)	Urethane	50	-20 to 180	28
Urethane Pre-Molded Wide Joint Seal (P)	Urethane	25	-20 to 180	45
Non-Sag, Acrylic Latex Caulking Compound (NS)(I)	Acrylic	7.5	0 to 180	20
Non-Skinning Butyl Sealant (NS)(I)	Butyl	-	-	N/A
Butyl Rubber Sealant (NS)(I)	Butyl	5	0 to 180	N/A
Two-Part Polysulfide Rubber Sealant (NS)(II)	Polysulfide	25	-20 to 180	50
High Performance Acrylic Latex (NS)(I)	Acrylic	25	0 to 180	25
AAMA Approved High Performance Acrylic Latex (NS)(I)	Acrylic	25	0 to 180	25
Glaziers & Contractors Silicone Sealant (NS)(I)	Silicone	25	-75 to 400	60
Non-Staining Technology™, Silicone Glazing & Weatherproofing Sealant (NS)(I)	Silicone	50	-60 to 300	50
High Performance Silicone Window & Door Sealant (NS)(I)	Silicone	50	-60 to 300	55
Ultra Fast Curing Window & Door Sealant (NS)(I)	Silicone	25	-60 to 300	45
High Impact Silicone (NS)(I)	Silicone	25	-60 to 300	120
Semi-Self Leveling Silicone Narrow-Joint Seam Sealer (SL)(I)	Silicone	50	-60 to 300	N/A
Thermal Barrier Silicone® (NS)(I)	Silicone	50	-60 to 300	55
Thermal Barrier Silicone® Narrow-Joint Seam Sealer (SL)(I)	Silicone	50	-60 to 300	N/A
Structural Silicone Sealant (NS)(II)	Silicone	25	-60 to 300	110
Narrow-Joint Seam Sealer (NS)(I)	Silicone	N/A	-60 to 300	20
Pre-Formed Silicone Profile Seal (P)	Silicone	200	-60 to 300	70
100% Pre-Formed Silicone Transition Membrane (P)	Silicone	200	-60 to 300	180
High Impact Silicone (NS)(I)	Silicone	25	-60 to 300	120
Flexible Polyurethane Security Sealant (NS)(II)	Urethane	12.5	-20 to 180	180
Flexible STPU Security Sealant (NS)(I)	STPU	12.5	-20 to 180	120
Epoxy Security Sealant (NS)(II)	Epoxy	N/A	-20 to 160	N/A
General Purpose Polyurethane Sealant (NS)(II)	Urethane	50	-20 to 180	28



Pecora is a member and supports:
SWRI, CSI, AIA, ICRI, ABAA, USGBC, IPI

Pecora is ISO 9001:2008 certified.

The Pecora promise is about more than high quality sealants, air barriers, and traffic coatings. It's a promise to you, to your project, to your reputation. We're hands-on and always here when you need us. Ready to make recommendations, answer questions, work through decisions, and help you find the best solution for your job. It's a promise of partnership.

Since its founding in 1862 as a Philadelphia-based paint and varnish company, Pecora has developed and manufactured trusted solutions to meet every customer's need. Over the years, the company used its innovative technological development capabilities to grow its product line and quickly emerge as a premier manufacturer of architectural weatherproofing products. Pecora is ISO 9001:2008 certified and proudly manufactures all products right here in the USA.



Contact Pecora Technical Services to learn how Pecora products can contribute to LEED, Green Globes, Living Building Challenge, and other green building rating systems.

165 Wambold Road, Harleysville, PA 19438 | 800.523.6688 | pecora.com

SEALANTS

TRAFFIC COATINGS

AIR BARRIERS

PRODUCT NAME	Expansion & Control	Waterproofing	Non-Structural Glazing	Structural Glazing	Shop Glazing	Window Beading	High Impact	Highway	Pedestrian	Vehicular	Airfield	Parking Area	Deck Coatings	Acoustical	Below Grade	Chemical Resistance	Firestopping	Food Processing-USA	Perimeter	Potable Water	Sanitary	Security	Water Immersion	Wall Coatings	APPLICABLE STANDARDS
FIRE-RATED UL SEALANTS*																									
AC-20 FTR®																									ASTM C834, UL, USDA
Dynaflex	●								●	●								●	●	●			●	●	ASTM C920, TT-S-00227E, UL, ASTM C1247, USDA
Dynatrol® II	●								●	●		●			●			●	●	●			●		ASTM C920, TT-S-00227E, UL, USDA
Dynatred®	●								●	●		●			●			●	●	●			●		ASTM C920, C1247, TT-S-00227E, UL, USDA
Pecora 864NST	●		●															●	●	●					ASTM C920, TT-S-001543A, 19-GP9, USDA
TRAFFIC SEALANTS																									
Pecora 300-SL	●							●	●	●	●	●						●							ASTM C920, DOT (By State), TT-S-001543A, D5893, USDA
Pecora 301-NS	●							●	●	●	●	●						●							ASTM C920, DOT (By State), TT-S-001543A, D5893, USDA
Pecora 310-SL	●								●	●		●						●							ASTM C920, TT-S-001543A, USDA
Pecora 311-NS	●								●	●		●						●							ASTM C920, TT-S-001543A, USDA
Pecora 322-FC	●							●	●	●	●														ASTM C920, TT-S-001543A, TT-S-0023C
Dynaflex	●								●	●								●	●	●			●	●	ASTM C920, TT-S-00227E, UL, ASTM C1247, USDA
Dynatred®	●								●	●		●			●			●	●	●			●		ASTM C920, ASTM C1247, TT-S-00227E, UL, USDA
Dynaspan	●								●	●		●													ASTM C920, TT-S-00227E
Dynatrol® II-SG	●								●	●		●						●							ASTM C920, TT-S-00227E
Urexpan™ NR-200	●								●	●		●													ASTM C920, TT-S-00227E
Urexpan™ NR-201	●								●	●		●						●							ASTM C920, TT-S-00230C, USDA
Synthacalk™ GC2+	●															●		●		●			●		ASTM C920, ASTM C1247, NSF61 SECTION 6, USDA
ACOUSTIC SEALANTS																									
AIS-919															●			●	●						ASTM C919, C834, E90, C217, USDA
BA-98															●										ASTM C-919, ASTM E-90, AAMA 809.2
AC-20 FTR®															●		●	●	●						ASTM C834, UL, USDA
Dynatrol® II	●								●	●		●			●		●	●	●				●		ASTM C920, TT-S-00227E, UL
WATER REPELLENTS/WALL COATINGS																									
Klere-Seal 9100-S		●						●	●	●	●	●													NCHRP - 244
Klere-Seal 910-W/920-W		●						●	●	●	●	●													FSSW - 110, NCHRP - 244
Klere-Seal 940-S VOC		●						●	●	●	●	●													NCHRP - 244
Weatherclad™																							●		ASTM E96, ASTM D2370, ASTM D3960
AIR, VAPOR & WATER RESISTIVE BARRIER SYSTEM																									
AVB Silicone		●																●	●						ASTM C920, USDA, UL
XL-Flash	●	●																							ASTM C920, TT-S-0023C, UL
XL-Perm ^{air} ™ VP		●																							ASTM E2357, ASTM E2178, UL
XL-Span		●																●	●						ASTM C1523, USDA
TRAFFIC COATING SYSTEM																									
Pecora-Deck 800 Series		●							●	●		●	●												ASTM C957
Pecora-Deck 800 FC Series		●							●	●		●	●												ASTM C957

* All sealants used as a component of a UL listed assembly