

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 08, 2019

1 Identification

- **Product identifier**
- **Trade name:** Pecora 300 SL Silicone Pavement Sealant
- **Other means of identification:** No other identifiers
- **Recommended use and restriction on use**
- **Recommended use:** Self-Leveling Pavement Joint Sealant
- **Restrictions on use:** No relevant information available.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
Pecora Corporation
165 Wambold Road
Harleysville, PA 19438
215-723-6051
- **Emergency telephone number:**
CHEMTREC
1-800-424-9300 (US/Canada)

2 Hazard(s) identification

- **Classification of the substance or mixture**
Flam. Liq. 4 H227 Combustible liquid.
Skin Sens. 1 H317 May cause an allergic skin reaction.
Repr. 2 H361 Suspected of damaging fertility or the unborn child.
STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms:**



GHS07 GHS08

- **Signal word:** Warning
- **Hazard statements:**
H227 Combustible liquid.
H317 May cause an allergic skin reaction.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.
- **Precautionary statements:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from flames and hot surfaces. – No smoking.
P260 Do not breathe mist/vapors/spray.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection.
P302+P352 If on skin: Wash with plenty of water.
P308+P313 IF exposed or concerned: Get medical advice/attention.

(Cont'd. on page 2)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 08, 2019

Trade name: Pecora 300 SL Silicone Pavement Sealant

(Cont'd. of page 1)

- P314 Get medical advice/attention if you feel unwell.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P363 Wash contaminated clothing before reuse.
- P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards** There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Components:**

1317-65-3	Limestone	20-40%
64741-65-7	Naphtha (petroleum), heavy alkylate <ul style="list-style-type: none"> ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ Skin Irrit. 2, H315; STOT SE 3, H336 	<10%
34036-80-1	2-butanone-O,O',O''-(phenylsilylydyne)trioxime <ul style="list-style-type: none"> ⚠ STOT RE 2, H373 ⚠ Skin Sens. 1, H317 	<5%
556-67-2	octamethylcyclotetrasiloxane <ul style="list-style-type: none"> ⚠ Flam. Liq. 3, H226 ⚠ Repr. 2, H361 	<1%

· **Additional information:**

For the wording of the listed Hazard Statements, refer to section 16.

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

· **After skin contact:**

Wash with soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

· **After eye contact:**

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** Do not induce vomiting; immediately call for medical help.

· **Most important symptoms and effects, both acute and delayed:**

Gastric or intestinal disorders when ingested.

Nausea in case of ingestion.

Slight irritant effect on eyes.

Slight irritant effect on skin and mucous membranes.

(Cont'd. on page 3)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 08, 2019

Trade name: Pecora 300 SL Silicone Pavement Sealant

(Cont'd. of page 2)

Allergic reactions

- **Danger:**
Suspected of damaging fertility or the unborn child.
May cause damage to organs through prolonged or repeated exposure.
- **Indication of any immediate medical attention and special treatment needed:** Treat symptomatically.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray.
- **For safety reasons unsuitable extinguishing agents:** None.
- **Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation.
Use personal protective equipment as required.
Keep away from ignition sources.
- **Environmental precautions**
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Methods and material for containment and cleaning up**
Towel or mop up material and collect in a suitable container.
For larger spills, add non-combustible inert binding material, then sweep up and discard.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling**
- **Precautions for safe handling:**
Open and handle receptacle with care.
Keep out of reach of children.
Avoid contact with the eyes and skin.
Keep away from open flame or other ignition sources.
- **Conditions for safe storage, including any incompatibilities**
- **Requirements to be met by storerooms and receptacles:**

(Cont'd. on page 4)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 08, 2019

Trade name: Pecora 300 SL Silicone Pavement Sealant

(Cont'd. of page 3)

- Store in cool, dry conditions in well sealed receptacles.
- Avoid storage near extreme heat, ignition sources or open flame.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Specific end use(s)** No relevant information available.

8 Exposure controls/personal protection

· Control parameters

· Components with limit values that require monitoring at the workplace:

1317-65-3 Limestone

PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV (USA)	TLV withdrawn

556-67-2 octamethylcyclotetrasiloxane

WEEL (USA)	Long-term value: 10* ppm *OARS WEEL
------------	--

· Exposure controls

· General protective and hygienic measures:

- The usual precautionary measures for handling chemicals should be followed.
- Keep away from foodstuffs, beverages and feed.
- Avoid contact with the eyes and skin.
- Avoid breathing mist, vapors, or spray.
- Pregnant women should strictly avoid inhalation or skin contact.

· Engineering controls: No relevant information available.

· Breathing equipment:

- Not required under normal conditions of use.
- Use suitable respiratory protective device in case of insufficient ventilation.
- NIOSH or EU approved dust respirator should be used for operations generating dust.

· Protection of hands:

- Wear protective gloves to handle contents of damaged or leaking units.
- Gloves are advised for repeated or prolonged contact.

· Eye protection: Follow relevant national guidelines concerning the use of protective eyewear.

· Body protection: Protective work clothing

· Limitation and supervision of exposure into the environment

- Avoid release to the environment.

· Risk management measures No special requirements.

9 Physical and chemical properties

· Information on basic physical and chemical properties

· Appearance:

Form:	Paste
Color:	Gray

(Cont'd. on page 5)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 08, 2019

Trade name: Pecora 300 SL Silicone Pavement Sealant

(Cont'd. of page 4)

· Odor:	Slight Solvent-like
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Melting point/Melting range:	Not determined.
· Boiling point/Boiling range:	Not determined.
· Flash point:	>60 °C (>140 °F)
· Flammability (solid, gaseous):	Not applicable.
· Auto-ignition temperature:	Not determined.
· Decomposition temperature:	Not determined.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits	
Lower:	Not determined.
Upper:	Not determined.
· Oxidizing properties:	Non-oxidizing.
· Vapor pressure:	Not determined.
· Density:	
Relative density:	Not determined.
Vapor density:	Not determined.
Evaporation rate:	<1
· Solubility in / Miscibility with Water:	Soluble.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity	
Dynamic:	Not determined.
Kinematic:	Not determined.
· VOC content:	90 g/l (<3%)
· Other information	No relevant information available.

10 Stability and reactivity

- **Reactivity:** No relevant information available.
- **Chemical stability:** Stable under normal temperatures and pressures.
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**
Reacts with strong acids.
Reacts with oxidizing agents.
- **Conditions to avoid** Excessive heat.
- **Incompatible materials**
Oxidizers
Strong acids

(Cont'd. on page 6)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 08, 2019

Trade name: Pecora 300 SL Silicone Pavement Sealant

(Cont'd. of page 5)

· **Hazardous decomposition products**

Under fire conditions only:
Nitrogen oxides (NOx)
Carbon monoxide and carbon dioxide
Hydrocarbons

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

64741-65-7 Naphtha (petroleum), heavy alkylate

Oral	LD50	>6000 mg/kg (rat)
Dermal	LD50	>3000 mg/kg (rabbit)
Inhalative	LC50/4h	>7.8 mg/l (rat)

· **Primary irritant effect:**

· **On the skin:** Based on available data, the classification criteria are not met.

· **On the eye:** Based on available data, the classification criteria are not met.

· **Sensitization:** Sensitization possible through skin contact.

· **IARC (International Agency for Research on Cancer):**

Present in trace quantities.

14808-60-7	Quartz	1
1333-86-4	Carbon black	2B
111-42-2	2,2'-iminodiethanol	2B

· **NTP (National Toxicology Program):**

Present in trace quantities.

14808-60-7	Quartz	K
------------	--------	---

· **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

· **Probable route(s) of exposure:**

Ingestion.
Eye contact.
Skin contact.

· **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.

· **Carcinogenicity:** Based on available data, the classification criteria are not met.

· **Reproductive toxicity:** Suspected of damaging fertility or the unborn child.

· **STOT-single exposure:** Based on available data, the classification criteria are not met.

· **STOT-repeated exposure:** May cause damage to organs through prolonged or repeated exposure.

· **Aspiration hazard:** Based on available data, the classification criteria are not met.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity** Harmful to aquatic life with long lasting effects.

· **Persistence and degradability** No relevant information available.

(Cont'd. on page 7)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 08, 2019

Trade name: Pecora 300 SL Silicone Pavement Sealant

(Cont'd. of page 6)

- **Bioaccumulative potential:** No relevant information available.
- **Mobility in soil:** No relevant information available.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Smaller quantities can be disposed of with household waste.
The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.
- **Uncleaned packagings**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	
· DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.
· UN proper shipping name	
· DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.
· Transport hazard class(es)	
· DOT, ADR/RID/ADN, IMDG, IATA	
· Class	Not regulated.
· Packing group	
· DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.
· Environmental hazards	
· Marine pollutant:	No
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	Classified as combustible under US DOT regulations. Labeling is only required for single packages ≥119 US gal / 450 L.

(Cont'd. on page 8)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 08, 2019

Trade name: Pecora 300 SL Silicone Pavement Sealant

(Cont'd. of page 7)

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· **Section 302 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients are listed.

· **TSCA (Toxic Substances Control Act)**

All ingredients are listed or exempt.

· **Proposition 65 (California)**

· **Chemicals known to cause cancer:**

Present in trace quantities.

Reference to carbon black and quartz is based on unbound respirable particles and is not generally applicable to product as supplied.

14808-60-7	Quartz
------------	--------

1333-86-4	Carbon black
-----------	--------------

111-42-2	2,2'-iminodiethanol
----------	---------------------

· **Chemicals known to cause developmental toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity for males:**

Present in trace quantities.

110-54-3	n-hexane
----------	----------

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **EPA (Environmental Protection Agency):**

None of the ingredients are listed.

· **IARC (International Agency for Research on Cancer):**

Present in trace quantities.

14808-60-7	Quartz	1
------------	--------	---

1333-86-4	Carbon black	2B
-----------	--------------	----

111-42-2	2,2'-iminodiethanol	2B
----------	---------------------	----

· **Canadian Domestic Substances List (DSL): (Substances not listed.)**

All ingredients are listed or exempt.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any
(Cont'd. on page 9)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 08, 2019

Trade name: Pecora 300 SL Silicone Pavement Sealant

(Cont'd. of page 8)

specific product features and shall not establish a legally valid contractual relationship.

· **Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bio-accumulable, Toxic
vPvB: very Persistent and very Bioaccumulative
OSHA: Occupational Safety & Health Administration
Flam. Liq. 3: Flammable liquids – Category 3
Flam. Liq. 4: Flammable liquids – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1

· **Sources**

Website, European Chemicals Agency (echa.europa.eu)
Website, US EPA Substance Registry Services (ofmpub.epa.gov/sorinternet/registry/substreg/home/overview/home.do)
Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)
Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6
Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.
Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com