

PRODUCT NAME	PRODUCT DESCRIPTION		PROPERTIES / SPECIFICATIONS			
	NON-SAG=(NS) SELF-LEVELING=(SL) PRE-FORMED=(P) SPRAYABLE=(S)	ML = MULTI-LAMINATE SYSTEM 1 PART = (I) 2 PART = (II)	COMPOSITION	MOVEMENT CLASS	SERVICE TEMPERATURE (°F)	MODULUS, TENSILE AT 100% EXTENSION (PSI)
SEALANTS:						
Pecora 864NST	▶	Non-Staining Technology™, Architectural Silicone Sealant (NS)(I)	Silicone	50	-60 to 300	35
Pecora 890NST	▶	Non-Staining Technology™, Ultra Low-Modulus Silicone Sealant (NS)(I)	Silicone	100	-60 to 300	25
Pecora 895NST	▶	Non-Staining Technology™, Silicone Glazing & Weatherproofing Sealant (NS)(I)	Silicone	50	-60 to 300	45
Pecora 898NST	▶	Non-Staining Technology™, Sanitary Mildew Resistant Silicone Sealant (NS)(I)	Silicone	50	-60 to 300	45
Pecora 890FTS	▶	Field Tintable Silicone® (NS)(I)	Silicone	100	-60 to 300	25
Pecora 890FTS-TXTR	▶	Field Tintable Textured Silicone® (NS)(I)	Silicone	50	-60 to 300	120
Pecora Contractor Silicone - PCS	▶	One-part, Architectural Silicone Sealant (NS)(I)	Silicone	50	-60 to 300	35
Silspan	▶	Pre-formed Silicone Profile Seal (P)	Silicone	200	-60 to 300	70
Dynatrol® I-XL	▶	General Purpose Polyurethane Sealant (NS)(I)	Urethane	25	-20 to 180	50
Dynatrol® I-XL Tru-White	▶	STPU Silicone/Urethane One-Part Hybrid (NS)(I)	STPU	50	-40 to 195	50
Dynatrol® II	▶	General Purpose Polyurethane Sealant (NS)(II)	Urethane	50	-20 to 180	28
Dynaspan	▶	Urethane Pre-Molded Wide Joint Seal (P)	Urethane	25	-20 to 180	45
AC-20® + Silicone	▶	Non-Sag, Acrylic Latex Caulking Compound (NS)(I)	Acrylic	7.5	0 to 180	20
BA-98	▶	Non-Skinning Butyl Sealant (NS)(I)	Butyl			N/A
BC-158	▶	Butyl Rubber Sealant (NS)(I)	Butyl	5	0 to 180	N/A
Synthacalk GC2+	▶	Two-Part Polysulfide Rubber Sealant (NS)(II)	Polysulfide	25	-20 to 180	50
Tilt-seal™	▶	High Performance Acrylic Latex (NS)(I)	Acrylic	25	0 to 180	25
GLAZING:						
AVW920™	▶	AAMA Approved High Performance Acrylic Latex (NS)(I)	Acrylic	25	0 to 180	25
Pecora 860	▶	Glaziers & Contractors Silicone Sealant (NS)(I)	Silicone	25	-75 to 400	60
Pecora 895NST	▶	Non-Staining Technology™, Silicone Glazing & Weatherproofing Sealant (NS)(I)	Silicone	50	-60 to 300	45
Pecora 896	▶	High Performance Silicone Window & Door Sealant (NS)(I)	Silicone	50	-60 to 300	45
Pecora 896FC	▶	Ultra Fast Curing Window and Door Sealer (NS)(I)	Silicone	25	-60 to 300	45
Pecora 896-HIS	▶	High Impact Silicone (NS)(I)	Silicone	25	-60 to 300	120
Pecora 896-SSL	▶	Semi-Self Leveling Silicone Narrow-Joint Seam Sealer (SL)(I)	Silicone	50	-60 to 300	N/A
Pecora 896-TBS	▶	Thermal Barrier Silicone® (NS)(I)	Silicone	50	-60 to 300	55
Pecora 896-TBS-SSL	▶	Thermal Barrier Silicone® Narrow-Joint Seam Sealer (SL)(I)	Silicone	50	-60 to 300	N/A
Pecora 985	▶	Structural Silicone Sealant (NS)(II)	Silicone	25	-60 to 300	75
Pecora 1215	▶	Narrow Joint Seam Sealer (NS)(I)	Silicone	N/A	-60 to 300	20
Silspan	▶	Pre-formed Silicone Profile Seal (P)	Silicone	200	-60 to 300	70
XL-Span	▶	100% Pre-formed Silicone Transition Membrane (P)	Silicone	200	-60 to 300	180
SECURITY SEALANTS:						
Pecora 896-HIS	▶	High Impact Silicone (NS)(I)	Silicone	25	-60 to 300	120
Dynaflex	▶	Flexible Polyurethane Security Sealant (NS)(II)	Urethane	12.5	-20 to 180	180
Dynaflex SC	▶	Flexible STPU Security Sealant (NS)(I)	STPU	12.5	-20 to 180	120
Dynapoxy™ EP-1200	▶	Epoxy Security Sealant (NS)(II)	Epoxy	N/A	-20 to 160	N/A
Dynatrol® II	▶	General Purpose Polyurethane Sealant (NS)(II)	Urethane	50	-20 to 180	28

PRODUCT NAME	Expansion / Control Joints	Waterproofing	Non-structural Glazing	Structural Glazing	Shop Glazing	Window Bedding	High Impact	Highway	Pedestrian	Vehicular	Airfield	Parking Area	Deck Coatings	Acoustical	Below Grade	Chemical Resistance	Firestopping	Food Processing- USDA	Perimeter	Potable Water	Sanitary	Security	Water Immersion	Wall Coatings	APPLICABLE SPECIFICATIONS	
SEALANTS:																										
Pecora 864NST																									ASTM C920, TT-S-001543A, 19-GP9, USDA	
Pecora 890NST																										ASTM C920, TT-S-001543A, 19-GP9, USDA
Pecora 895NST																										ASTM C920, TT-S-001543A, 19-GP9, USDA, ASTM C1184
Pecora 898NST																										ASTM C920, TT-S-001543A, USDA
Pecora 890FTS																										ASTM C920, TT-S-001543A, 19-GP9, USDA
Pecora 890FTS-TXTR																										ASTM C920, TT-S00230C, 19GP-9, USDA
Pecora Contractor Silicone - PCS																										ASTM C920, TT-S-230C, CGSB-19GP-9, USDA
Silspan																										ASTM C1523, USDA
Dynatrol® I-XL																										ASTM C920, C1247, NSF61, 00230C, USDA
Dynatrol® I-XL Tru-White																										ASTM C920, USDA
Dynatrol® II																										ASTM C920, TT-S-00227E, UL
Dynaspan																										ASTM C920, TT-S-00227E
AC-20® + Silicone																										ASTM C834, USDA
BA-98																										ASTM C919, ASTM E-90, AAMA 809.2
BC-158																										ASTM C1311, TT-S-001657
Synthacalk GC2+																										ASTM C920, C1247, NSF61 SECTION 6, USDA
Tilt-seal™																										ASTM C920, ASTM C834, USDA
GLAZING:																										
AVW920™																										ASTM C920, ASTM C834, USDA
Pecora 860																										ASTM C920, TT-S-001543A, FDA, NSF51
Pecora 895NST																										ASTM C920, TT-S-001543A, 19-GP9, USDA, ASTM C1184
Pecora 896																										ASTM C1184-91, C920, TT-S-001543A, USDA, ASTM C1184
Pecora 896FC																										TT-S-001543A, TT-S-00230C, ASTM C-920, ASTM C1184
Pecora 896-HIS																										AAMA 506.0, TT-S 230C, Class A, ASTM C920, ASTM C1184
Pecora 896-SSL																										AAMA 803.3-07, Type II
Pecora 896-TBS																										ASTM C1184-91, C920, TT-S-001543A, USDA, ASTM C1184
Pecora 896-TBS-SSL																										AAMA 803.3-07, Type II
Pecora 985																										ASTM C920, USDA, ASTM C1184
Pecora 1215																										AAMA 803.3-07, Type I & II
Silspan																										ASTM C1523, USDA
XL-Span																										ASTM C1523, USDA
SECURITY SEALANTS:																										
Pecora 896-HIS																										AAMA 506.0, TT-S 230C, Class A, ASTM C920, ASTM C1184
Dynaflex																										ASTM C920, TT-S-00227E, UL, ASTM C1247
Dynaflex SC																										ASTM C920, TT-S-00230C, USDA
Dynapoxy™ EP-1200																										ASTM C881, Type I, USDA
Dynatrol® II																										ASTM C920, TT-S-00227E, UL

PRODUCT NAME	PRODUCT DESCRIPTION				PROPERTIES / SPECIFICATIONS			
	NON-SAG=(NS)	SELF-LEVELING=(SL)	PRE-FORMED=(P)	SPRAYABLE=(S)	COMPOSITION	MOVEMENT CLASS	SERVICE TEMPERATURE (°F)	MODULUS, TENSILE AT 100% EXTENSION (PSI)
FIRE-RATED UL SEALANTS:*								
AC-20 FTR®	Acoustical & Insulation Sealant (NS)(I)				Acrylic	7.5	N/A	20
Dynaflex	Flexible Polyurethane Security Sealant (NS)(II)				Urethane	12.5	-20 to 180	180
Dynatrol® II	General Purpose Polyurethane Sealant (NS)(II)				Urethane	50	-20 to 180	28
Dynatred®	Non-Sag, Traffic-Grade Polyurethane Sealant (NS)(II)				Urethane	25	-20 to 180	55
Pecora 864NST	Non-Staining Technology™, Architectural Silicone Sealant (NS)(I)				Silicone	50	-60 to 300	35
TRAFFIC SEALANTS:								
Pecora 300-SL	Self-Leveling Pavement Joint Sealant (SL)(I)				Silicone	100	-60 to 300	9
Pecora 301-NS	Non-Sag Pavement Joint Sealant (NS)(I)				Silicone	100	-60 to 300	15
Pecora 310-SL	Self-Leveling Parking Deck Sealant (SL)(I)				Silicone	100	-60 to 300	9
Pecora 311-NS	Non-Sag Parking Deck Sealant (NS)(I)				Silicone	100	-60 to 300	15
Pecora 322FC	Fast Cure Traffic Silicone (SL)(II)				Silicone	100	-60 to 300	180
Dynaflex	Flexible Polyurethane Security Sealant (NS)(II)				Urethane	12.5	-20 to 180	180
Dynatred®	Non-Sag, Traffic-Grade Polyurethane Sealant (NS)(II)				Urethane	25	-20 to 180	55
Dynaspan	Urethane Pre-Molded Wide Joint Seal (P)				Urethane	25	-20 to 180	45
Dynatrol® II-SG	Self-Leveling Polyurethane Slope Grade (5% & 15%), Traffic-Grade Sealant (SL)(II)				Urethane	25	-20 to 180	45
Urexpan™ NR-200	Self-Leveling, Traffic-Grade Polyurethane Sealant (SL)(II)				Urethane	25	-20 to 180	45
Urexpan™ NR-201	Self-Leveling, Traffic Grade Hybrid STPU Sealant (SL)(I)				STPU	25	-20 to 180	75
Synthacalk™ GC2+	Two-Part Polysulfide Rubber Sealant (NS)(II)				Polysulfide	25	-20 to 180	50
ACOUSTIC SEALANTS:								
AIS-919	Acoustical & Insulation Latex Sealant (NS/S)(I)				Acrylic	7.5	0 to 180	20
BA-98	Non-Skinning Butyl Sealant (NS)(I)				Butyl			N/A
AC-20 FTR®	(Fire and Temperature Rated) Acoustical & Insulation Sealant (NS)(I)				Acrylic	7.5	N/A	20
Dynatrol® II	General Purpose Polyurethane Sealant (NS)(II)				Urethane	50	-20 to 180	28
WATER REPELLENTS/ WALL COATINGS:								
Klere-Seal 9100-S	Silane Penetrating Clear Sealer (S)(I)				Silane	N/A	N/A	N/A
Klere-Seal 910-W/920-W	Water-Based Penetrating Sealer (S)(II)				Siloxane	N/A	N/A	N/A
Klere-Seal 940-S VOC	Silane Penetrating Sealer (S)(I)				Silane	N/A	N/A	N/A
Weatherclad™	Elastomeric Acrylic Wall Coating (S)(I)				Acrylic	N/A	-15 to 180	N/A
AIR, VAPOR & WATER RESISTIVE BARRIER SYSTEM:								
AVB Silicone	Primerless Silicone Sealant for Air Vapor Barrier Surface Transitions (NS)(I)				Silicone	25	-60 to 300	33
XL-Flash	Liquid Applied Flashing and Joint Filler (NS)(I)				STPU	12.5	-20 to 180	250
XL-Perm ^{ULTRA} VP	Fluid Applied, Permeable STPU Air, Vapor & Water Resistive Barrier (S)(I)				STPU	N/A	-20 to 180	30
XL-Span	100% Pre-formed Silicone Transition Membrane (P)				Silicone	200	-60 to 300	180
TRAFFIC COATING SYSTEM:								
Pecora-Deck 800 Series	Elastomeric Deck Coating System (SL)(ML)				Urethane	N/A	-20 to 180	N/A
Pecora-Deck 800 FC Series	Low VOC Low VOC, Fast Cure Elastomeric Deck Coating System (SL)(ML)				Urethane	N/A	-20 to 180	N/A

* All sealants used as a component of a UL listed assembly



Contact Pecora Technical Services to learn how Pecora products can contribute to LEED, Green Globes, Living Building Challenge, and other green building rating systems.

PRODUCT NAME	Expansion / Control Joints	Waterproofing	Non-structural Glazing	Structural Glazing	Shop Glazing	Window Bedding	High Impact	Highway	Pedestrian	Vehicular	Airfield	Parking Area	Deck Coatings	Acoustical	Below Grade	Chemical Resistance	Firestopping	Food Processing- USDA	Perimeter	Potable Water	Sanitary	Security	Water Immersion	Wall Coatings	APPLICABLE SPECIFICATIONS
FIRE-RATED UL SEALANTS:*																									
AC-20 FTR®														◆			◆	◆	◆						ASTM C834, UL, USDA
Dynaflex	◆								◆	◆							◆	◆	◆				◆	◆	ASTM C920, TT-S-00227E, UL, ASTM C1247
Dynatrol® II	◆								◆	◆		◆		◆	◆		◆	◆	◆				◆		ASTM C920, TT-S-00227E, UL
Dynatred®	◆								◆	◆		◆		◆	◆		◆	◆	◆				◆		ASTM C920, C1247, TT-S-00227E, UL
Pecora 864NST	◆		◆															◆	◆	◆					ASTM C920, TT-S-001543A, 19-GP9, USDA
TRAFFIC SEALANTS:																									
Pecora 300-SL	◆							◆	◆	◆	◆	◆						◆							ASTM C920, DOT (By State), TT-S-001543A, D5893, USDA
Pecora 301-NS	◆							◆	◆	◆	◆	◆						◆							ASTM C920, DOT (By State), TT-S-001543A, D5893, USDA
Pecora 310-SL	◆								◆	◆		◆						◆							ASTM C920, TT-S-001543A, USDA
Pecora 311-NS	◆								◆	◆		◆						◆							ASTM C920, TT-S-001543A, USDA
Pecora 322FC	◆							◆	◆	◆	◆														ASTM C920, TT-S-001543, TT-S-0023C
Dynaflex	◆								◆	◆							◆	◆	◆			◆	◆		ASTM C920, TT-S-00227E, UL, ASTM C1247
Dynatred®	◆								◆	◆		◆		◆	◆		◆	◆	◆				◆		ASTM C920, C1247, TT-S-00227E, UL
Dynaspan	◆								◆	◆		◆													ASTM C920, TT-S-00227E
Dynatrol® II-SG	◆								◆	◆		◆						◆							ASTM C920, TT-S-00227E
Urexpan™ NR-200	◆								◆	◆		◆													ASTM C920, TT-S-00227E
Urexpan™ NR-201	◆								◆	◆		◆						◆							ASTM C920, TT-S-00230C, USDA
Synthacalk™ GC2+	◆														◆		◆		◆				◆		ASTM C920, C1247, NSF61 SECTION 6, USDA
ACOUSTIC SEALANTS:																									
AIS-919														◆				◆	◆						ASTM C919, C834, E90, C217, USDA
BA-98														◆											ASTM C-919, ASTM E-90, AAMA 809.2
AC-20 FTR®														◆			◆	◆	◆						ASTM C834, UL, USDA
Dynatrol® II	◆								◆	◆		◆		◆	◆		◆	◆	◆				◆		ASTM C920, TT-S-00227E, UL
WATER REPELLENTS/ WALL COATINGS:																									
Klere-Seal 9100-S		◆						◆	◆	◆	◆	◆													NCHRP - 244
Klere-Seal 910-W/920-W		◆						◆	◆	◆	◆	◆													FSSW - 110, NCHRP - 244
Klere-Seal 940-S VOC		◆						◆	◆	◆	◆	◆													NCHRP - 244
Weatherclad™																							◆		ASTME96, ASTM D2370, ASTM D3960
AIR, VAPOR & WATER RESISTIVE BARRIER SYSTEM:																									
AVB Silicone		◆																◆	◆						ASTM C920, USDA, UL
XL-Flash	◆	◆																							ASTM C-920, TT-S-0023C, UL
XL-Perm ^{ULTRA} VP		◆																							ASTM E2357, ASTM E2178, UL
XL-Span		◆																◆	◆						ASTM C1523, USDA
TRAFFIC COATING SYSTEM:																									
Pecora-Deck 800 Series		◆							◆	◆		◆	◆												ASTM C957
Pecora-Deck 800 FC Series		◆							◆	◆		◆	◆												ASTM C957

* All sealants used as a component of a UL listed assembly



Contact Pecora Technical Services to learn how Pecora products can contribute to LEED, Green Globes, Living Building Challenge, and other green building rating systems.