



# Green Building Certification Data

MasterFormat Designation: 07 92 00 – Joint Sealants

June 27, 2017

**RE: Pecora DynaFlex™ SC Flexible Polyurethane Security Sealant**

Pecora Corporation hereby declares the following information for Pecora DynaFlex™ SC:

## LEED® 2009 and LEED® v4:

**MR Credit Building Product Disclosure and Optimization—Sourcing of Raw Materials, Option 2 (\*MR Credit 4.1 and 4.2, Recycled Content):** For the purposes of the LEED Rating System Pecora DynaFlex™ SC contains 0% recycled content.

**MR Credit Building Product Disclosure and Optimization—Sourcing of Raw Materials, Options 1 and 2 (\*MR Credit 5.1 and 5.2, Regional Materials):** Pecora DynaFlex™ SC is manufactured in Harleysville, PA 19438. Due to the complexity of its raw material supply chain, the point source of Pecora DynaFlex™ SC's material ingredients cannot be determined.

**EQ Credit Low-Emitting Materials, Options 1 and 2 (\*IEQ Credit 4.1, Low-Emitting Materials—Adhesives & Sealants):**

**VOC Content:** Pecora DynaFlex™ SC contains 15 g/L volatile organic compound (VOC) content, well below the 250 g/L VOC limit set by South Coast Air Quality Management District (SCAQMD) Rule 1168 (effective 7/1/2005) for architectural sealants.

**VOC Emissions (LEED v4 and LEED 2009 for Schools):** Pecora DynaFlex™ SC has been tested and meets the interior air quality (IAQ) emissions requirements for the classroom, private office, and new single-family residential scenarios of CDPH Standard Method v1.1-2010 (California Specification 01350). After 14 days (336 hours), the total VOC was <2 µg (0.002 mg)/m<sup>3</sup>, well within the lowest of three prescribed TVOC ranges.

\* LEED 2009 credits and options (June 30, 2021 sunset date)

## Green Globes for New Construction

**Criterion 3.7.2.1 Volatile Organic Compounds:** Pecora DynaFlex™ SC contains 15 g/L volatile organic compound (VOC), well below the 250 g/L VOC limit set by South Coast Air Quality Management District (SCAQMD) Rule 1168 for architectural sealants.

## Living Building Challenge<sup>SM</sup> 3.0

**Imperative 08 Healthy Interior Environment:** Pecora DynaFlex™ SC has been tested and meets the interior air quality (IAQ) emissions requirements for the classroom, private office, and new single-family residential scenarios of CDPH Standard Method v1.1-2010 (California Specification 01350). After 14 days (336 hours), the total VOC was <2 µg (0.002 mg)/m<sup>3</sup>.

**Imperative 10 Red List:** Contact the Technical Services Department.

'USGBC' and related logo is a trademark owned by the U.S. Green Building Council and is used by permission.





Should you require additional information, please contact the Technical Services Dept. at 1-800-355-8817 or [techservices@pecora.com](mailto:techservices@pecora.com).

Sincerely,

A handwritten signature in black ink that reads 'Steven T. Lawrey'.

Steven T. Lawrey AIA, CSI, CCPR, CCS, CCCA, LEED® AP  
Building Science Engineer  
Pecora Corporation

'USGBC' and related logo is a trademark owned by the U.S. Green Building Council and is used by permission.

