



Green Building Certification Data

MasterFormat Designations: 07 25 00 – Weather Barriers; 07 27 00 – Air Barriers; 07 27 26 – Fluid-Applied Membrane Air Barriers

June 27, 2017

RE: Pecora XL-Flash STPU Fast Curing Liquid Flashing & Joint Filler

Pecora Corporation hereby declares the following information for Pecora XL-Flash:

LEED® v4 and LEED® 2009:

MR Credit Building Product Disclosure and Optimization—Sourcing of Raw Materials, Option 2 (*MR Credit 4.1 and 4.2, Recycled Content): For the purposes of the LEED Rating System Pecora XL Flash contains 0% recycled content.

MR Credit Building Product Disclosure and Optimization—Sourcing of Raw Materials, Options 1 and 2 (*MR Credit 5.1 and 5.2, Regional Materials): Pecora XL Flash is manufactured in Harleysville, PA 19438. Due to the complexity of its raw material supply chain, the point source of Pecora XL Flash's material ingredients cannot be determined.

EQ Credit Low-Emitting Materials, Options 1 and 2 (*IEQ Credit 4.1, Low-Emitting Materials—Adhesives & Sealants):

VOC Content: Pecora XL Flash contains 15 g/L volatile organic compound (VOC) content, well below the 250 g/L VOC limit set by South Coast Air Quality Management District (SCAQMD) Rule 1168 (effective 7/1/2005) for architectural sealants.

VOC Emissions (LEED v4 [including exterior applied products for healthcare and schools projects] and LEED 2009 for Schools): Pecora XL Flash has been tested and meets the interior air quality (IAQ) emissions requirements for the classroom, private office, and new single-family residential scenarios of CDPH Standard Method v1.1-2010 (California Specification 01350). After 14 days (336 hours), the total VOC was <2 µg (0.002 mg)/m³, well within the lowest of three prescribed TVOC ranges.

* LEED 2009 credits and options (June 30, 2021 sunset date)

Green Globes for New Construction

Criterion 3.7.2.1 Volatile Organic Compounds: Pecora XL Flash contains 15 g/L volatile organic compound (VOC), well below the 250 g/L VOC limit set by South Coast Air Quality Management District (SCAQMD) Rule 1168 for architectural sealants.

Living Building ChallengeSM 3.0

Imperative 08 Healthy Interior Environment: Pecora XL Flash Pecora 895NST has been tested and meets the interior air quality (IAQ) emissions requirements for the classroom, private office, and new single-family residential scenarios of CDPH Standard Method v1.1-2010 (California Specification 01350). After 14 days (336 hours), the total VOC was <2 µg (0.002 mg)/m³.

Imperative 10 Red List: Contact the Technical Services Department.

'USGBC' and related logo is a trademark owned by the U.S. Green Building Council and is used by permission.





Should you require additional information, please contact the Technical Services Department at 1-800-523-6688 or techservices@pecora.com.

Sincerely,

A handwritten signature in black ink that reads 'Steven T. Lawrey'.

Steven T. Lawrey AIA, CSI, CCPR, CCS, CCCA, LEED® AP
Building Science Engineer
Pecora Corporation

'USGBC' and related logo is a trademark owned by the U.S. Green Building Council and is used by permission.

