



Green Building Certification Data

February 16, 2021

RE: Pecora 300 SL Self-Leveling Silicone Highway and Pavement Joint Sealant

Pecora Corporation hereby declares the following information for Pecora 300 SL.

General:

CSI Designation: 07 97 00 Joint Sealants

Sealant Product Category: 300 SL is classified as a Roadway Sealant in accordance with Federal, regional, and state air quality model rules or regulations

LEED® v4, v4.1, and LEED® 2009:

MR Credit Building Product Disclosure and Optimization—Sourcing of Raw Materials, Option 2 (*MR Credit 4.1 and 4.2, Recycled Content): For the purposes of the LEED Rating System Pecora 300 SL contains 0% recycled content.

MR Credit Building Product Disclosure and Optimization—Sourcing of Raw Materials, Options 1 and 2 (*MR Credit 5.1 and 5.2, Regional Materials): Pecora 300 SL is manufactured in Harleysville, PA 19438. Due to the complexity of its raw material supply chain, the point source of Pecora 300 SL's material ingredients cannot be determined.

EQ Credit Low-Emitting Materials, Options 1 and 2 (*IEQ Credit 4.1, Low-Emitting Materials—Adhesives & Sealants):

VOC Content: Pecora 300 SL contains 40 g/L volatile organic compound (VOC) content, below the 250 g/L VOC limit set by the respective amendments to South Coast Air Quality Management District (SCAQMD) Rule 1168 for roadway sealants

LEED 2009 and LEED v4: July 1, 2005 amendment.

LEED v4.1: February 6, 2017 amendment.

VOC Emissions (LEED v4 and LEED 2009 for Schools): As of the date of this disclosure, Pecora 300 SL has not been tested per the California Department of Public Health (CDPH) Standard Method (California Specification 01350).

* LEED 2009 credits and options (June 30, 2022 sunset date)

Green Globes for New Construction 2019

Criterion 6.2.1.1 (ANSI 11.2.1.1) Volatile Organic Compounds:

VOC Content: Pecora 300 SL contains 40 g/L and less than 250 g/L volatile organic compound (VOC) content limit set by South Coast Air Quality Management District (SCAQMD) Rule 1168 (January 7, 2005) for roadway sealants.

VOC Emissions: As of the date of this disclosure, Pecora 300 SL has not been tested per the California Department of Public Health (CDPH) Standard Method (California Specification 01350).





Living Building ChallengeSM 3.1

Imperative 08 Healthy Interior Environment: As of the date of this disclosure, Pecora 300 SL has not been tested per the California Department of Public Health (CDPH) Standard Method (California Specification 01350).

Imperative 10 Red List: Pecora 300 SL contains one listed ingredient.

Ozone Transport Commission Model Rule:

Model Rule for Adhesives and Sealants: The VOC content of Pecora 300 SL is 40 g/L, below the 250 g/L VOC limit set by the OTC AIM Model Rule (effective January 1, 2009) for Roadway Sealants and therefore, complies with the OTC model rule.

US Environmental Protection Agency: No adhesives and sealants rule.

Should you require additional information, please contact the Technical Services Department at 1-800-523-6688 or techservices@pecora.com.

Sincerely,

Steven T. Lawrey AIA, CSI, CCPR, CCS, CCCA, LEED® AP
Building Science Engineer
Pecora Corporation





'USGBC' and related logo is a trademark owned by the U.S. Green Building Council and is used by permission.

