

OPTIONAL - EXTEND FLEXIBLE FLASHING AROUND FRAMING

ROUGH OPG FLEXIBLE FLASHING: PECORA XL-WRAP TWF (4" WIDTH)

BACKER ROD & APP'D. PECORA SEALANT

FLANGE WINDOW UNIT w/ NAIL FIN

2" MIN

2" MIN

FRAMED & SHEATHED EXTERIOR WALL CONSTRUCTION

INTERIOR

LINE OF AIR & MOISTURE CONTROL LAYERS

EXTERIOR

AIR, VAPOR, or WEATHER BARRIER (AVB) MEMBRANE

SEAL ALL EDGES w/ PECORA AVB SILICONE, XL-FLASH, or DYNATROL I-XL HYBRID

PRIME SUBSTRATE w/PECORA WraPrime WHERE REQ'D by APPL'N INSTRUCTIONS

NAIL FIN FLEXIBLE FLASHING: PECORA XL-WRAP TWF (6" WIDTH SHOWN - USE 9" WIDTH for COMPLIANCE w/ASTM E2112)

BACKER ROD & APPROVED PECORA SILICONE, HYBRID, or URETHANE SEALANT

EXTERIOR WALL VENEER



PECORA CORPORATION

Architectural Weatherproofing Products
U.S.A. • since 1862

Pecora Corporation is a manufacturer of materials and not a licensed design professional. Details prepared by Pecora are schematic only and are offered as a guide for the convenience of Pecora's customers.

07 65 00 FLEXIBLE FLASHING / B2010.80 EXT WALL SUPP COMPONENTS
**XL-WRAP TWF SELF-ADHERING THRU-WALL FLASHING
FLANGE WINDOW JAMB DETAL**

NO SCALE

REV: 12-2021

DRAWING NO.: PEC-TWF-FIN-002