

PRODUCT	DESCRIPTION Non-Sag (NS) - Self Leveling (SL) - Pre-Formed (P) - Sprayable (S) Multi-Laminate System (ML) - 1 Part (I) - 2 Part (II)	PROPERTIES/SPECIFICATIONS						CATEGORIES																APPLICABLE STANDARDS						
		Composition	Movement Class (%)	Service Temperature °F	Modulus (Tensile at 100% extension (PSI))	Expansion & Control Joints	Door & Window Perimeter	Non-Structural Glazing	Structural Glazing	Shop Glazing	Window Bedding	High Impact	Highway	Pedestrian	Vehicular	Airfield	Parking Area	Acoustical	Below Grade	Chemical Resistance	Firestopping	Food Processing- USDA	Potable Water			Sanitary	Security	Water Immersion	Deck Coating	Waterproofing
FIRE-RATED UL SEALANTS (07 84 00)																														
AC-20 FTR®	Acoustical & Insulation Sealant (NS)(I)	Acrylic	75	0 to 180	20	●											●			●	●									ASTM C834, C919, E90; UL263, 1479, ASTM E119, E814, NFPA 251; USDA
Dynaflex	Flexible Polyurethane Security Sealant (NS)(II)	Urethane	12.5	-20 to 180	180	●	●						●	●						●	●			●	●					ASTM C920, C1247, TT-S-00227E; UL263, ASTM E119, NFPA 251; USDA
Dynatrol® II	General Purpose Polyurethane Sealant (NS)(II)	Urethane	50	-20 to 180	28	●	●						●	●	●					●	●			●						ASTM C920, C1247, TT-S-00227E; UL263, ASTM E119, NFPA 251; USDA; CAN/CGSB 19.24
Dynatred®	Non-Sag, Traffic-Grade Polyurethane Sealant (NS)(II)	Urethane	25	-20 to 180	55	●	●						●	●		●				●	●				●	●				ASTM C920, C1247, TT-S-00227E; UL263, ASTM E119, NFPA 251; USDA
864NST	Non-Staining Technology™, Architectural Silicone Sealant (NS)(I)	Silicone	50	-60 to 300	38	●	●	●												●	●									ASTM C920, C1248, TT-S-001543A, TT-S-00230C; UL263, ASTM E119, NFPA 251; 19-GP9; USDA
TRAFFIC SEALANTS (07 92 00 / 32 12 72 / 32 13 72)																														
300-SL	Self-Leveling Pavement Joint Sealant (SL)(I)	Silicone	100	-60 to 300	9	●						●	●	●	●	●					●									ASTM C920, DOT (By State), TT-S-001543A, ASTM D5893, FAA Brief 36, USDA
301-NS	Non-Sag Pavement Joint Sealant (NS)(I)	Silicone	100	-60 to 300	15	●						●	●	●	●	●					●									ASTM C920, DOT (By State), TT-S-001543A, ASTM D5893, FAA Brief 36, USDA
322-FC	Fast Cure Traffic Silicone (SL)(II)	Silicone	100	-60 to 300	13	●						●	●	●	●	●					●									ASTM C920, TT-S-001543A, TT-S-0023C, ASTM D5893, USDA
Dynaflex	Flexible Polyurethane Security Sealant (NS)(II)	Urethane	12.5	-20 to 180	180	●	●						●	●						●	●			●	●					ASTM C920, C1247, TT-S-00227E; UL263, ASTM E119, NFPA 251; USDA
Dynatred®	Non-Sag, Traffic-Grade Polyurethane Sealant (NS)(II)	Urethane	25	-20 to 180	55	●	●						●	●		●				●	●			●	●					ASTM C920, C1247, TT-S-00227E; UL263, ASTM E119, NFPA 251; USDA
Dynaspan	Pre-molded Expansion Joint Cover Assembly (P)	Urethane	25	-20 to 180	45	●							●	●		●														ASTM C920, TT-S-00227E
Dynatrol® II-SL	Self-Leveling Polyurethane Slope Grade (5% & 15%), Traffic-Grade Sealant (SL)(II)	Urethane	50	-20 to 180	75	●							●	●		●					●									ASTM C920, TT-S-00227E, SS-S-195B, SS-S-159B, USDA
Urexpan™ NR-201	Self-Leveling, Traffic-Grade Hybrid STPU Sealant (SL)(I)	STPU	25	-20 to 180	75	●							●	●		●					●									ASTM C920, TT-S-00230C, USDA
Synthacalk™ GC2+	Two-Part Polysulfide Rubber Sealant (NS)(II)	Polysulfide	25	-0 to 180	50	●	●						●	●		●		●		●	●			●						ASTM C920, ASTM C1247, NSF61 SECTION 6, USDA
ACOUSTIC SEALANTS (07 92 19)																														
AIS-919	Acoustical & Insulation Latex Sealant (NS/S)(I)	Acrylic	75	0 to 180	20		●										●				●									ASTM C834, C919, E90, USDA
BA-98	Non-Skinning Butyl Sealant (NS)(I)	Butyl	-	0 to 160	N/A			●		●	●						●				●									ASTM C919, E90, AAMA 809.2, USDA
AC-20 FTR®	(Fire and Temperature Rated) Acoustical & Insulation Sealant (NS)(I)	Acrylic	75	0 to 180	20		●										●			●	●									ASTM C834, C919, E90, E119, E814, UL263, UL1479, USDA
Dynatrol® II	General Purpose Polyurethane Sealant (NS)(II)	Urethane	50	-20 to 180	28	●	●						●	●		●	●				●			●						ASTM C920, C1247, TT-S-00227E; UL263, ASTM E119, NFPA 251; USDA; CAN/CGSB 19.24
WATER REPELLENTS/WALL COATINGS (07 19 00 / 09 96 00)																														
Klere-Seal 9100-S	Silane Penetrating Clear Sealer (S)(I)	Silane	N/A	N/A	N/A								●	●	●	●	●													NCHRP - 244
Klere-Seal 910-W/920-W	Water-Based Penetrating Sealer (S)(II)	Silane Siloxane	N/A	N/A	N/A								●	●	●	●	●													Fed Spec SSW-110, NCHRP - 244
Klere-Seal 940-S VOC	Silane Penetrating Sealer (S)(I)	Silane	N/A	N/A	N/A								●	●	●	●	●													NCHRP - 244
WeatherClad™	Elastomeric Acrylic Wall Coating (S)(I)	Acrylic	N/A	-15 to 180	N/A																						●			
WeatherClad™ WT	Exterior-Grade Architectural Wall Coating	Acrylic	N/A	-15 to 180	N/A																						●			
SilcoPrime	STPU-Based Primer for Architectural Wall Coatings (S)(I)	STPU	N/A	-20 to 180	N/A																									
AIR, VAPOR & WATER RESISTIVE BARRIER SYSTEM (07 25 00 / 07 27 00 / 07 27 26)																														
XL-Perm ULTRA NP	Fluid Applied, Non-Permeable STPU Air, Vapor & Water Resistive Barrier (S)(I)	STPU	N/A	-20 to 180	15																					●	●			ASTM E2357, ASTM E2178; ABAA Evaluated
XL-Perm ULTRA VP	Fluid Applied, Permeable STPU Air, Vapor & Water Resistive Barrier (S)(I)	STPU	N/A	-20 to 180	30																					●	●			ASTM E2357, ASTM E2178, UL Des No EWS0024; ABAA Evaluated
ProPerm VP	Fluid Applied, Permeable Water Borne, Air and Vapor Barrier	Acrylic	N/A	0 to 180	32																					●	●			ASTM E2357, ASTM E2178; ABAA Evaluated
XL-Flash	Liquid Applied Flashing and Joint Filler (NS)(I)	STPU	12.5	-20 to 180	120																●					●	●			ASTM C920, TT-S-0023C, UL Des No EWS0024, USDA
AVB Silicone	Primerless Silicone Sealant for Air Vapor Barrier Surface Transitions (NS)(I)	Silicone	25	-60 to 300	33	●	●														●					●	●			ASTM C920, USDA, UL Des No EWS0024
XL-Span	100% Pre-Formed Silicone Transition Membrane (P)	Silicone	200	-60 to 300	180	●	●														●					●	●			ASTM C1523, USDA
XL-Wrap TWF	Foil-Faced, Self-Adhering Membrane Flashing with Butyl Adhesive (P)	Foil/HDPE/Butyl	N/A	-45 to 300	N/A		●											●								●	●			
TRAFFIC COATINGS (07 18 00)																														
Pecora-Deck 800	Standard Elastomeric Deck Coating System (ML)	Urethane	N/A	-20 to 180	N/A									●	●						●					●	●			ASTM C957, USDA
Pecora-Deck HB1000	High Build, Fast Cure, Industrial Grade Traffic Bearing Membrane (ML)	Urethane	N/A	-20 to 180	N/A									●	●			●			●					●	●			ASTM C957, USDA
Pecora-Deck HB1100-SA	Single Coat Polyurethane Waterproofing & Traffic Bearing Coating (ML)	Urethane	N/A	-20 to 180	N/A									●	●						●					●	●			ASTM C957, USDA
Pecora Deck-Seal	Traffic Grade Polyurethane Sealant	Urethane	25	-20 to 180	65	●								●	●						●									ASTM C920, TT-S-00230C, CAN/CGSB 1913-M87, USDA