

OPTIONAL - EXTEND FLEXIBLE
FLASHING AROUND FRAMING

ROUGH OPG FLEXIBLE
FLASHING: PECORA
XL-WRAP TWF (4" WIDTH)

BACKER ROD & APP'D.
PECORA SEALANT

FLANGE WINDOW UNIT
w/ NAIL FIN

2"
MIN

2"
MIN

FRAMED & SHEATHED EXTERIOR
WALL CONSTRUCTION

INTERIOR

LINE OF AIR & MOISTURE
CONTROL LAYERS

EXTERIOR

AIR, VAPOR, or WEATHER BARRIER (AVB)
MEMBRANE

SEAL ALL EDGES w/ PECORA AVB SILICONE,
XL-FLASH, or DYNATROL I-XL HYBRID

PRIME SUBSTRATE w/PECORA WraPrime
WHERE REQ'D by APPL'N INSTRUCTIONS

NAIL FIN FLEXIBLE FLASHING: PECORA
XL-WRAP TWF (6" WIDTH SHOWN - USE 9"
WIDTH for COMPLIANCE w/ASTM E2112)

BACKER ROD & APPROVED PECORA
SILICONE, HYBRID, or URETHANE SEALANT

EXTERIOR WALL VENEER



**PECORA
CORPORATION®**

Architectural Weatherproofing Products
U.S.A. • since 1862

Pecora Corporation is a
manufacturer of materials
and not a licensed design
professional. Details
prepared by Pecora are
schematic only and are
offered as a guide for the
convenience of Pecora's
customers.

07 65 00 FLEXIBLE FLASHING / B2010.80 EXT WALL SUPP COMPONENTS
**XL-WRAP TWF SELF-ADHERING THRU-WALL FLASHING
FLANGE WINDOW JAMB DETAL**

NO SCALE

REV: 4-9-2024

DRAWING NO.: PEC-TWF-FIN-002