

OPTIONAL - EXTEND WRB/AIR
BARRIER AROUND FRAMING

INSUL. (NOT BY PECORA)

FLANGE WINDOW W/
NAILING FIN

EXTEND WRB/AIR
BARRIER INWARD
MIN 2" PAST INT.
AIR SEAL

2"
MIN

ROUGH OPENING CORNER
FLASHING: PECORA XL-PERM
(ULTRA) VP - APPLY AT 30-40
WET MILS

2"
MIN

FRAMED & SHEATHED EXTERIOR
WALL CONSTRUCTION

INTERIOR

LINE OF AIR & MOISTURE
CONTROL LAYERS

EXTERIOR

WEATHER BARRIER, VAPOR RETARDER, AIR
BARRIER: PECORA XL-PERM (ULTRA) VP
APPLY AT 10-14 WET MILS (8-12 MILS DFT)

EXTERIOR WALL VENEER

BED MOUNTING FLANGE IN 1/2" BEAD OF
PECORA AVB SILICONE SEALANT

FORM SEALANT BRIDGE FROM MOUNTING
FLANGE TO WRB/AIR BARRIER W/ PECORA
AVB SILICONE SEALANT

OPEN-CELL BACKER ROD & APP'D PECORA
SILICONE, HYBRID, OR URETHANE SEALANT

NOTES:

1. FILL SUBSTRATE GAPS & VOIDS WITH PECORA XL-FLASH.
2. COORDINATE THIS DETAIL WITH ARCHITECTURAL DWGS.



*Pecora Corporation is a
manufacturer of materials
and not a licensed design
professional. Details
prepared by Pecora are
schematic only and are
offered as a guide for the
convenience of Pecora's
customers.*

07 27 00 AIR BARRIERS / B2010.80 EXTERIOR WALL SUPP COMPONENTS
XL-PERM (ULTRA) VP
FLANGE WINDOW w/XL-PERM CORNER FLASHING

NO SCALE

REV: 4-1-2024

DRAWING NO.: PEC-VP-FIN-002