

STRIKE MORTAR
JOINTS FLUSH

2"
MIN.

LIQUID FLASHING & JOINT FILLER: PECORA
XL-FLASH - APPLY TO SUBSTRATE AT
20-40 WET MILS

2"
MIN.

WEATHER BARRIER, VAPOR RETARDER,
AIR BARRIER: PECORA XL-PERM (ULTRA) VP
APPLY TO SUBSTRATE AT 10-14 WET MILS
(8-12 MILS DFT)

LIQUID FLASHING & JOINT FILLER: PECORA
XL-FLASH - APPLY TO SUBSTRATE AT
20-40 WET MILS

2"
MIN.

FORM 1/2" CANT BEAD W/ PECORA XL-FLASH

WEATHER BARRIER, VAPOR RETARDER,
AIR BARRIER: PECORA XL-PERM (ULTRA) VP
APPLY AT 10-14 WET MILS (8-12 MILS DFT)

CAST-IN-PLACE CONCRETE,
PRECAST CONCRETE, OR
UNIT MASONRY EXTERIOR
WALL CONSTRUCTION

2"
MIN.

LINE OF AIR, VAPOR, & WATER
CONTROL LAYERS

EXTERIOR

INTERIOR



**PECORA
CORPORATION®**

Architectural Weatherproofing Products
U.S.A. • since 1862

*Pecora Corporation is a
manufacturer of materials
and not a licensed design
professional. Details
prepared by Pecora are
schematic only and are
offered as a guide for the
convenience of Pecora's
customers.*

07 27 00 AIR BARRIERS / B2010.80 EXTERIOR WALL SUPP COMPONENTS
XL-PERM (ULTRA) VP
INSIDE & OUTSIDE CORNERS-CONCRETE & MASONRY

NO SCALE

REV: 4-1-2024

DRAWING NO.: PEC-VP-IOC-002